Zipper Closure Version

If you'd rather have a zipper closure instead of a magnetic snap closure, follow the modifications below. There are a few changes to the cutting instructions and you'll need to skip over the magnetic snap instructions and instead follow the Inset Zipper Panel instructions on the following pages.

CUTTING FABRIC

Follow the cutting instructions on Pages 1-2, except follow the instructions below for cutting the Interior fabric:

Interior

5/8 yd for interior front and back for inset zipper panel version

- Cut two pieces 16-1/2" H x 20" W for interior front and back
- Cut two pieces 4" H x 16" W for interior inset zipper panel pieces
- For a 1" wide zipper, cut one piece 2" H x 4-1/2" W for the zipper tab OR
- For a 1-1/2" wide zipper, cut one piece 2-1/2" H x 4-1/2" W for the zipper tab

CUTTING INTERFACING

Cut all of the interfacing pieces listed on Pages 2-3 except as follows:

Firm Interfacing

- Omit magnetic snap reinforcements
- Also cut two pieces 3-1/2" H x 15" W to stabilize interior inset zipper panel pieces. Center on wrong side of fabric and fuse according to manufacturer's directions.

Medium weight interfacing

The size of the interior front and interior back interfacing changes:

• Cut two pieces 16-1/2" H x 20" W to stabilize interior front and back for zipper version.

Stabilizer

• No changes

SEWING

Follow the sewing instructions for the Magnetic Snap Version starting on Page 3 through Steps 1 and 2 of the Interior section on Page 7.

Skip the Magnetic Snap Installation steps, Steps 3 and 4 of the Interior section. Instead, follow the section Inset Zipper Panel on Page 10.

The page to the left is a replacement page for print versions copyrighted 2016.